



## SPECIFICATIONS

# 808 Filter Changer

The 808 Filter Changer is designed to filter dissolution samples from six, seven or eight lines simultaneously and can store up to 200 filters at a time. The Agilent 808 must be used in conjunction with the 806 Syringe Pump and can easily be added to an existing configuration that includes the 8000 Dissolution Sampling Station.



### 808 Filter Changer Specifications

Altitude	0 - 2000 m (0 - 6562 ft.)
Temperature	5 to 40 °C
Humidity (non-condensing)	Not more than 80% RH
Sampling accuracy with 8000 and 806 Syringe Pump	± 0.3 mL (3%)
Minimum sample interval with 8000 and 806 Syringe Pump	6 min
Sample volume with 8000 and 806 Syringe Pump	1-14 mL
Filter type with 8000 and 806 Syringe Pump	25 mm automation compatible filters > 0.45 µm*
Voltage requirements	115 V / 60 Hz 230 V / 50 Hz
Current requirements	115 V—2.0 Amp 230 V—2.0 Amp
Fuse requirements	115 V—2.0 Amp, 250 V, 5 x 20 mm 230 V—2.0 Amp, 250 V, 5 x 20 mm
Dimensions	Height: 45.1 cm (17.75 in.) Width: 24.13 cm (9.5 in.) Depth: 44.45 cm (17.5 in.)
Equipment weight	14.2 kg (31.2 lbs.)

\*Due to sample matrix, pre-filtration with Full Flow Filters may also be required.

### Ordering Information

Product Description	Part Number
808 Filter Changer, 8-channel, 115V	15-5002
808 Filter Changer, 6-channel, 115V	15-5004
808 Filter Changer, 8-channel, 230V	15-5006
808 Filter Changer, 6-channel, 230V	15-5008

This information is subject to change without notice.  
© Agilent Technologies, Inc. 2011  
Printed in U.S.A., August 31, 2011  
5990-7404EN

To learn more about Dissolution Testing,  
visit us at [www.agilent.com/lifesciences/dissolution](http://www.agilent.com/lifesciences/dissolution)

