

# Frying Fat Analysis with Agilent PLgel Columns and Gel Permeation Chromatography

# **Application Note**

Food Testing and Agriculture

# **Author**

Graham Cleaver
Agilent Technologies, Inc.

### Introduction

During the frying process, a wide variety of chemical reactions results in the formation of compounds with high molecular weight. The presence of air in the frying system and the heating of fats initiate a cycle of thermal and thermo-oxidative decomposition that results in the formation of polymeric compounds. The quality and properties of the fats are dependent on the levels of these higher molecular weight materials.

Gel permeation chromatography (GPC), which separates components based on molecular size in solution, provides an appropriate method for the quantification of such compounds in oils and fats.

# **Frying Oil Analysis**

Typical separations of triglycerides from plant and animal sources are shown in Figures 1 and 2. The column type selected, Agilent PLgel 5  $\mu$ m 100Å, has an exclusion limit of 4,000 molecular weight (polystyrene equivalent), and a guaranteed column efficiency of greater than 60,000 plates/m.

For peak detection, a conventional differential refractometer can be used (as shown in Figure 1). As an alternative, an evaporative light scattering detector can provide improved sensitivity and baseline stability to aid quantification (see Figure 2). An outline of the method and its validation has been published in an IUPAC paper [1].





# **Conditions for Figure 1**

Columns 2 × Agilent PLgel 5 µm 100Å, 7.5 × 300 mm

(p/n PL1110-6520)

Eluent THF

Flow rate 0.5 mL/min

Detector RI

System Agilent PL-GPC 50




Figure 1. Fish oil analyzed on an Agilent PLgel 5 μm two-column set with refractive index detection.

# **Conditions for Figure 2**

Columns  $2 \times Agilent PLgel 5 \mu m 100 Å, 7.5 \times 300 mm$ 

(p/n PL1110-6520)

Eluent THF

Flow rate 0.5 mL/min

Detector Agilent ELSD

System PL-GPC 50




Figure 2. Grape seed oil separated on an Agilent PLgel 5 μm two-column set with evaporative light scattering detection to provide baseline stability and improved sensitivity compared to refractive index detection

## **Conclusion**

Gel permeation chromatography with Agilent PLgel 5  $\mu$ m columns is an appropriate method for quantifying triglycerides in frying oils. If peak detection is the main requirement a conventional differential refractometer is perfectly adequate. However, for quantification an Agilent evaporative light scattering detector improves sensitivity and baseline stability.

### Reference

 P. Wolff, F. X. Mordret, and A. Dieffenbacher (1991)
 Determination of polymerized triglycerides in oils and fats by high performance liquid chromatography. Pure and Applied Chemistry, 63, No 8, 1163-1171.

### For More Information

These data represent typical results. For more information on our products and services, visit our Web site at www.agilent.com/chem.

## www.agilent.com/chem

Agilent shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this material.

Information, descriptions, and specifications in this publication are subject to change without notice.

© Agilent Technologies, Inc., 2015 Printed in the USA April 30, 2015 5990-8418EN

