

# SEC Analysis of Modified Hydroxyethyl Cellulose

## **Application Note**

#### **Author**

Graham Cleaver Agilent Technologies, Inc.

#### Introduction

Hydroxyethyl cellulose (HEC) is widely used by the cosmetic, paint, textile and pharmaceutical industries, for example, as a carrier gel for microbiocides. It is a non-ionic polymer with many useful properties as a thickening agent, stabilizer, emulsifier or dipersant, and it easily dissolves in hot and cold water. In addition, the water repellant properties of HEC can be improved to enhance its value to the manufacturers of waterproof textiles.

Modifying the hydrophobicity alters the molecular weight, and such changes can be assessed by size exclusion chromatography (SEC) with Agilent PL aquagel-OH 40 and 60 8  $\mu$ m columns.

These columns are ideal for the analysis of HEC, because they combine low exclusion limit, high pore volume and high column efficiency (>35,000 plates/ meter) for maximum resolution. In this case, two different PL aquagel-0H columns were connected in series to cover a molecular weight range from  $10^4$  to  $10^7$ . Column calibration was achieved using pullulan standards.





#### **Conditions**

Samples: Hydroxyethyl cellulose before and

after modification

Columns: 2 x PL aquagel-OH 60 8 µm,

300 x 7.5 mm (p/n PL1149-6860) + 1 x PL aquagel-OH 40 8  $\mu$ m, 300 x 7.5 mm (p/n PL-1149-6840)

Eluent: 0.05 M NaH<sub>2</sub>PO<sub>4</sub> + 0.25 M NaCl at

pH 7

Flow Rate: 1.0 mL/min

Detection: RI

### **Results and Discussion**

Figure 1 shows overlaid molecular weight distributions of a sample of HEC before and after modification to its hydrophobicity. Sample A is HEC. Sample B is Sample A after hydrophobic modification.




Figure 1. Overlaid MW distributions of a sample of HEC before and after modification

## **Conclusion**

SEC using PL aquagel-OH columns successfully resolved a sample of hydroxyethyl cellulose before and after hydrophobic modification. The 'neutral' surface and capability of operating across a wide range of eluent conditions equip PL aquagel-OH for the high performance analysis of analytes with neutral, ionic and hydrophobic moieties, singly or combined.

#### www.agilent.com/chem

This information is subject to change without notice.

© Agilent Technologies, Inc. 2015

Published in UK, April 30, 2015

5991-5793EN

