

IDENTIFICATION SHEET

Aqueous calibration solution ASTASOL®

ASTASOL[®] TUNE25

This Identification sheet is designed in accordance with ISO Guide 31

Category:	Traced reference materials
Analytes:	Ce, Co, Li, Mg, Tl, Y
Product code:	TUNE25

Starting primary compounds and theirs purities (%):

Ce(NO₃)₃. 6H₂O 99.99; Co 99.998; Li₂CO₃ 99.999; Mg 99.98; TlNO₃ 99.9995; Y₂O₃ 99.99

Matrix:

2% HNO₃ (v/v), prepared from sub boil distilled HNO₃ (ANALPURE[®]) and ultrapure demineralized water (resistivity $\geq 18 \text{ M}\Omega.\text{cm}, 0.22\mu\text{m}$ filtered)

Assigned concentration value and expanded uncertainty (k = 2) at 20 °C

$1.00 \pm 0.01 \ \mu g/l$ (each analyte)

Specification:

Batch No.: 1014

The date of production: 11.12.2023

Expiry date: 11.12.2024

Intended use:

As a calibrator of analytical methods analysing aqueous solutions such as atomic spectrometry (AAS, AES, ICP-OES, ICP-MS), molecular absorption spectrometry and selected electroanalytical methods.

Verze IL / Version of the IS: 01

1/3

Characterization and traceability:

This RM has an assigned value of concentration and uncertainty on the basis of gravimetric preparation. Traceability is realized with CRM AN 9011(1N), AN 9012(1N), AN 9030(1N), AN 9032(1N), AN 9062(1N) and AN 9067(1N), through a short unbroken chain of calibrations (AAS, AES, ICP-OES) or comparisons (primary analytical methods). All mentioned CRM AN are traceable to the corresponding SRMs NIST.

Trace impurities in bottled solution:

Max. 0.005 µg/l (total)

Homogeneity and stability:

It has been demonstrated that this RM is homogeneous and its stability is guaranteed during the whole shelf life provided the solution it kept under conditions presented below.

Storing and instruction for use:

This RM has to be stored in the original closed bottle between 5 - 30 °C. The producer guarantees a declared expiration time provided the RM is properly stored and professionally handled. The temperature of the solution must be 20 ± 0.5 °C before every use. It is important to cover the screw cap and the neck of the bottle with a parafilm layer after each opening to prevent vapour phase losses. It is not recommended to use the standard solution when the bottle contains less than 10 % of the solution. Therefore, in case of nontransparent bottle, it is important to indicate the amount of the solution used, e.g. on the label. Do not pippette from the bottle.

Producer:

ANALYTIKA[®], spol. s r.o. Department of reference materials Ke Klíčovu 2a/816 190 00 Prague 9 – Vysočany Czech Republic

www.analytika.net sales@analytika.net

Phone/Fax: +420 286 589 616

Verze IL / Version of the IS: 01

2/3

Quality management systems:

The Producer has a certified quality management system ČSN EN ISO 9001: 2016.

The Producer meets the requirements of ČSN EN ISO 17034:2017: General requirements for the competence of reference material producers.

Head of production department:

Petránhova'

Mgr. Mirka Petránková

Date of the first issue of IS: 11.12.2023 IS revision date: Revision of IS: Version of IS: 01

Verze IL / Version of the IS: 01

3/3

Verze formuláře / Version of the form: 03