

## **TOY20DAD 800 H**

## TWO CHANNEL UV DETECTOR FOUR CHANNEL UV DETECTOR SCANNING UV DETECTOR

is a standalone UV detector suited for preparative and flash chromatography with diode array (**DAD**) in range 190 – 800 nm. It is offered in the following versions:

Two Channel version measures at two wavelengths simultaneously with possibility to see current scan.

Four Channel version measures at four wavelengths simultaneously with possibility to see current scan.

Scanning version measures at four wavelengths simultaneously or sends scan with speed 20 Hz which allows to create 3D picture.



More wavelengths or scan are used in liquid chromatography to **verify purity of analyzed samples** or in situations when some peaks absorb on different wavelengths. **Most important features of TOY18DAD H detectors:** 

- built-in lamp working hours counter
- easy replacement of flow cell
- measuring at more wavelengths simultaneously
- sophisticated diagnostic software

## SPECIFICATION

	TOY20DAD 800 H Two Channel	TOY20DAD 800 H Four Channel	TOY20DAD 800 H Scanning
Part Number	T20H310Y	T20H320Y	T20H330Y
Wavelength range	190 – 800 nm (256 elements on CCD)		
Number of channels (Signals)	2	4	4
Scan	Informative 190 – 800 nm	Informative 190 – 800 nm	190 - 800 nm, 20 Hz, step 1 nm
Typical spectral half-width	10 nm		
Accuracy of adjustment / Reproducibility	± 1 nm / ±0.5 nm		
Noise level at test cell (254 nm, TC 0.75s)	± 5 x 10 <sup>-5</sup> AU		
Drift at test cell (254 nm after 1 h)	1 x 10 <sup>-3</sup> AU/hr		
Materials in contact with mobile phase	FEP; fused silica, stainless steel, PEEK, KEL-F		
Time constant (T63)	0.5 s, 0.75 s, 1.0 s, 2.0 s, 4.0 s, 8.0 s, 16.0 s, 0.2 s, 0.1 s		
Interface	RS232, USB, LAN		
Power supply	100-240 V		
Power input	100 VA		
Dimensions (W x H x D)	280 x 135 x 498 mm (11.02 x 5.32 x 19.61 in)		
Weight	7.5 kg (16.53 lb)		

## PREPARATIVE CELL PLCC 15L IN BRACKET (SUPPLIED WITH UNIT)

volume/optical path (adjustable)	40 μl / 0.3 mm	
Cell connecting	tubing with OD = 1/8", thread 1/4"-28	
Maximal flow rate	500 ml/min. (3 000 ml/min. with PLCC3L)	

ECOM spol. s r.o. +420 221 511 310