

# Thermo Scientific Vanquish – Fluorescence Detector F

Better separations, more results, easier interaction

Thermo Scientific™ Vanquish™ UHPLC system is designed to offer:

- **Better separations** with the power of the system to unveil more compounds than ever before
- **More results** with throughput, speed and sample capacity to boost workflow productivity
- **Easier interaction** to make the system a joy to work with

The Vanquish UHPLC system is designed as an integrated UHPLC system, with versatile detection options.



## Ultra-Sensitive Fluorescence Detection

The optical design of the Vanquish Fluorescence Detector provides you with the best detection sensitivity and superior signal-to-noise performance through highly effective stray light suppression. Thermal effects are reduced with temperature-controlled flow cells for increased detection precision.

The sophisticated design enables multiple measurement features for maximum effectiveness. Monitor up to four excitation/emission wavelength pairs simultaneously in multichannel operation mode or scan your chromatogram for the best emission/excitation wavelengths. Improve detection sensitivity and selectivity by ultrafast wavelength switching between peaks. The detector is easy to use and provides you with an unmatched detection experience.

- Acquire data at up to 200 Hz for best support of even fastest UHPLC separations
- Select from two biocompatible flow cells to match the requirements of your application – the 8  $\mu$ L flow cell for best trace detection or the 2  $\mu$ L flow cell for best chromatographic efficiency with narrow-bore HPLC and UHPLC columns
- Optimize your sensitivity by xenon flash lamp frequency and variable emission filter settings
- Benefit from an extended wavelength range up to 900 nm by the optional second photomultiplier (Dual-PMT)
- Simplify method development or improve existing methods using single spectrum scans or fluorescence field acquisition in excitation, emission, or synchronous mode
- Improve your costs of ownership by increased lamp lifetime due to the long-life xenon flash lamp and various lamp operation modes

**Thermo**  
SCIENTIFIC

## PRODUCT SPECIFICATIONS

Specification	Value															
Optical Design	Two monochromators w/ concave holographic gratings and elliptic mirrors for highest efficiency in light transmission															
Light Source	Xenon flash lamp															
Lamp Pulse Frequency	HighPower (~300 Hz); Standard (~100 Hz); LongLife (~20 Hz)															
Maximum Data Collection Rate	One channel: 200 Hz (under Thermo Scientific™ Dionex™ Chromeleon™ Chromatography Data System (CDS) software, version 7.2 control or later) Multiple channels: up to 4 Hz															
Spectrum Scanning Modes	Single Spectrum Scans or FL Field Acquisitions: Excitation, emission or synchronous mode (FL Fields under Chromeleon CDS 7.2 or later)															
Number of Signal Channels	Up to 4															
Wavelength Switching Time	<250 ms															
Wavelength Range	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Variant</th> <th>Ex Min</th> <th>Ex Max</th> <th>Em Min</th> <th>Em Max</th> </tr> </thead> <tbody> <tr> <td>VF-D50-A</td> <td>200</td> <td>630</td> <td>220</td> <td>650</td> </tr> <tr> <td>VF-D51-A (Dual-PMT)</td> <td>200</td> <td>880</td> <td>220</td> <td>900</td> </tr> </tbody> </table>	Variant	Ex Min	Ex Max	Em Min	Em Max	VF-D50-A	200	630	220	650	VF-D51-A (Dual-PMT)	200	880	220	900
Variant	Ex Min	Ex Max	Em Min	Em Max												
VF-D50-A	200	630	220	650												
VF-D51-A (Dual-PMT)	200	880	220	900												
Spectral Bandwidth (FWHM)	Excitation: 20 nm; Emission: 20 nm															
Wavelength Accuracy	±2 nm															
Wavelength Repeatability	±0.2 nm															
Emission Filter	Variable, 5 positions															
Sensitivity	Raman S/N: >550 ASTM over the entire lifetime of the lamp (>2100 using dark signal as noise reference)															
Flow Cell Thermostatting	15 °C above ambient to 50 °C absolute															
Flow Cells	Standard flow cell: 8 µL, biocompatible; 20 bar (290 psi) maximum cell pressure Micro flow cell: 2 µL, biocompatible; 40 bar (290 psi) maximum cell pressure															
GLP	Predictive performance functions: lamp age, leak detection, service monitoring period, grating and filter movements, PMT workload. All system parameters are logged in the Chromeleon CDS Audit Trail.															
PC Connection	USB 2.0; 3-port hub to connect further Vanquish modules															
I/O Interfaces	2 × 6 pin Mini-DIN connectors each having functionality: 1 input, 1 relay out															
Safety Features	Power-up diagnostics of optics, cooling fans, motors and electronics. Leak detection and safe leak handling.															
Wetted Parts	Fused silica, carbon reinforced PTFE, MP35N															
Biocompatible	Yes; pH range 2–12, chloride concentration up to 1 mol/L															
Environmental Conditions	5–35 °C; 20–80% RH (non-condensing)															
Power Requirements	100–240 V AC, 50/60 Hz, max. 150 W/255 VA															
Dimensions (h × w × d)	159 mm × 420 mm × 620 mm (6.3 in. × 16.5 in. × 24.4 in.)															
Weight	21 kg (46.3 lbs)															

## ORDERING INFORMATION

Description	Part Number
Vanquish Fluorescence Detector F	VF-D50-A
Vanquish Fluorescence Detector F with Dual-PMT	VF-D51-A
Accessories	
Standard Flow Cell, 8 µL, biocompatible	6079.4230
Micro Flow Cell, 2 µL, biocompatible	6079.4330
Dual-PMT Option	6078.5360
Flow Cell Syringe Injection Kit	6078.4200

To order in the U.S., call 1-800-346-6390, or contact the Thermo Fisher Scientific office nearest you. Outside the U.S., order through your local Thermo Fisher Scientific office or distributor. Refer to the following part numbers.

[www.thermofisher.com/chromatography](http://www.thermofisher.com/chromatography)

©2016 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

**Africa** +43 1 333 50 34 0  
**Australia** +61 3 9757 4300  
**Austria** +43 810 282 206  
**Belgium** +32 53 73 42 41  
**Brazil** +55 11 3731 5140  
**Canada** +1 800 530 8447  
**China** 800 810 5118 (free call domestic)  
 400 650 5118

**Denmark** +45 70 23 62 60  
**Europe-Other** +43 1 333 50 34 0  
**Finland** +358 10 3292 200  
**France** +33 1 60 92 48 00  
**Germany** +49 6103 408 1014  
**India** +91 22 6742 9494  
**Italy** +39 02 950 591

**Japan** +81 6 6885 1213  
**Korea** +82 2 3420 8600  
**Latin America** +1 561 688 8700  
**Middle East** +43 1 333 50 34 0  
**Netherlands** +31 76 579 55 55  
**New Zealand** +64 9 980 6700  
**Norway** +46 8 556 468 00

**Russia/CIS** +43 1 333 50 34 0  
**Singapore** +65 6289 1190  
**Sweden** +46 8 556 468 00  
**Switzerland** +41 61 716 77 00  
**Taiwan** +886 2 8751 6655  
**UK/Ireland** +44 1442 233555  
**USA** +1 800 532 4752

Thermo

SCIENTIFIC

A Thermo Fisher Scientific Brand