### thermoscientific

# SPE for biological fluids

### Author

Thermo Fisher Scientific

### **Keywords**

Solid phase extraction (SPE), sample prep, hypersep, SOLA

### Introduction

Sample preparation is a critical step prior to LC or GC analysis. Due to their nature, biological fluids such as serum, plasma, blood, and urine present a difficult challenge.

Solid Phase Extraction (SPE) can be used for three important purposes:

- Removal of interfering matrix components. This can help protect analytical instrumentation and columns from "dirty" biological samples
- Concentration of the sample to increase sensitivity of the analysis
- Transfer of analytes into a suitable solvent for analysis. This can help make the sample more compatible for analysis.

### Important notes

- For effective analyte retention, pre-treat and optimize the sample, ensure analytes are free in solution or choose an appropriate hydrolysis procedure, and remove excessive particulates via filtration or centrifugation.
- Dilute sample with an equal volume of water or suitable buffer prior to applying the sample to the SPE column/96-well plate. Buffer choice and pH considerations are dependent upon the compound of interest in the sample. If diluting in buffer, ensure the sample is at a proper pH for optimum retention.
- Capacity of the SPE devices are approximately between 1–5% of the sorbent bed weight. This needs to be verified with your individual sample.



**APPLICATION BRIEF 21937** 

### **Materials required**

- Appropriate solvents and buffers required for conditioning and washing the SPE columns/96-well plates
- Vacuum manifold, positive pressure manifold, or centrifuge
- Tubes, vials, or 96-well plates for collection of filtrates

## Reversed phase protocol for acidic, basic, and neutral compounds

- Condition SPE device with 2–5 column volumes of a strong solvent like methanol
- 2. Equilibrate with 2–5 column volumes of a weak solvent like water. Do not let packing bed dry before application of sample.
- 3. Apply sample and push or draw sample through the packing bed at a flowrate of about 1 mL/min
- 4. Wash off any weakly retained interferences with a weak polar solvent such as methanol/water; 5/95 (v/v)
- 5. Elute using a strong elution solvent such as methanol and collect for analysis

### Mixed mode cation exchange procedure for basic ionizable compounds

- 1. Condition SPE device with 2–5 column volumes of a strong solvent like methanol
- Equilibrate with 2–5 column volumes of water with 1% formic acid. Do not let packing bed dry before application of sample.
- 3. Apply sample and push or draw sample through the packing bed at a flowrate of about 1 mL/min

- 4. Wash off any weakly retained interferences using water with 1% formic acid
- 5. Elute using a strong elution solvent such as methanol with 1% ammonium hydroxide and collect for analysis

### Mixed mode anion exchange procedure for acidic ionizable compounds

- 1. Condition SPE device with 2–5 column volumes of a strong solvent like methanol
- Equilibrate with 2–5 column volumes of water with 1% ammonium hydroxide. Do not let packing bed dry before application of sample.
- 3. Apply sample and push or draw sample through the packing bed at a flowrate of about 1 mL/min
- 4. Wash off any weakly retained interferences using water with 1% ammonium hydroxide
- 5. Elute using a strong elution solvent such as methanol with 1% formic acid and collect for analysis

### **Recommended wash and elution volumes**

Sorbent Bed Weight	Recommended Wash and Elution Volume
2 mg	0.2 mL
10 mg	0.5 mL
30 mg	1–2 mL
60 mg	2–3 mL
200 mg	3–4 mL
500 mg	5–6 mL

### **Related products**

Description	Part Number
Thermo Scientific <sup>™</sup> Hypersep <sup>™</sup> Universal SPE Vacuum Manifold, for 96-well plate or 24/48 cartridges	60104-233
Thermo Scientific <sup>™</sup> Hypersep <sup>™</sup> Vacuum Pump, European version	60103-351
Thermo Scientific <sup>™</sup> Hypersep <sup>™</sup> Vacuum Pump, North American version	60104-243

Current versions of product instructions are available at separatedbyexperience.com/chromexpert

### Learn more about HyperSep SPE extraction and clean-up products at separatedbyexperience.com/chromexpert

© 2019 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific and its subsidiaries. This information is presented as an example of the capabilities of Thermo Fisher Scientific products. It is not intended to encourage use of these products in any manners that might infringe the intellectual property rights of others. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representatives for details. **AB21937-EN 0519M** 

