

Analysis of Carnauba Wax using an Agilent J&W FactorFour VF-5ht UltiMetal Column

Application Note

Author

John Oostdijk Agilent Technologies, Inc.

Introduction

Carnauba wax originates from the leaves of carnauba palm in Brazil. It is widely used in lipsticks, eyeliners and sun care preparations, automobile waxes, shoe and guitar polishes, and candies because of its glossy finish. The wax is a formulation aid in sauces, chewing gum and juices, a surface finishing agent in baked foods, and a tablet coating agent.

Carnauba wax contains mainly wax esters in the C46–C54 range with some small amounts of free acids, alcohols and resins. The VF-5ht UltiMetal column is ideal for the analysis of carnauba wax. This column has been developed using the proprietary UltiMetal technology that provides a virtually unbreakable metal column material with excellent inertness properties similar to fused silica tubing. The UltiMetal treated column tubing is coated with the VF-5 low bleed arylene stabilized phase resulting in a highly temperature stable and durable column perfectly suited for a variety of high temperature applications.

The C46–C54 wax esters of the carnauba wax elute in the 275 $^{\circ}$ C to 400 $^{\circ}$ C temperature range in this analysis, while the lighter free acids and alcohols fraction elutes between 220 $^{\circ}$ C and 250 $^{\circ}$ C.

The low bleed characteristics of this column, evident above 350 °C, allow the accurate quantification of minor high boiling impurities. The high maximum column temperatures enable a fast bake-out of highly retained sample material.



Conditions

Technique: GC-FID

Column: VF-5ht UltiMetal, 15 m x 0.32 mm,

Df = 0.1 μ m + Retention Gap, 2 m x 0.53 mm (part number CP9095)

Sample: Carnauba wax, saturated (approx

0.1 %) in CS2

Sample Size: 1.0 µL

Carrier Gas: Hydrogen, constant flow mode 10

 mL/min

Injector: On-column (1093), reversed liner,


100 °C (0 min) to 400 °C with 15

°C/min

Temperature: 50 °C (1 min) to 450 °C (20 mins)

with 10 °C / min

Detection: FID (HT), 400 °C



Analysis of carnauba wax using a VF-5ht UltiMetal column

www.agilent.com/chem

This information is subject to change without notice.

© Agilent Technologies, Inc. 2010

Published in UK, October 07, 2010

SI-01129

